

INTEGRATED POWER DELIVERY WITH FLEX CIRCUIT
INTERCONNECTION FOR HIGH DENSITY HIGH POWER CIRCUITS FOR
INTEGRATED CIRCUITS AND SYSTEMS

5

ABSTRACT OF THE DISCLOSURE

A method and apparatus for electrically interconnecting a first circuit board having a power conditioning circuit and a second circuit board having a power dissipating component disposed therebelow along a z (vertical) axis is disclosed. In an illustrative embodiment, the apparatus comprises a first flexible circuit having a first set of raised
10 conductive contacts, the first flexible circuit disposed on a first side of the second circuit board; and a second flexible circuit having a second set of raised conductive contacts, the second flexible circuit disposed on a second side of the second circuit board opposing the first side of the second circuit board. A power signal from the power conditioning circuit is provided to the second circuit board at least in part by one of the first set of raised
15 conductive contacts on the flexible circuit and the second set of raised conductive contacts on the second flexible circuit and a ground return is provided to the second circuit board by the other of the first set of raised conductive contacts on the first flexible circuit and the second set of raised conductive contacts on the second flexible circuit.

CERTIFICATE OF MAILING UNDER 37 CFR 1.10

Express Mail mailing label number: EL815947968US

Date of Deposit: December 4, 2001

I hereby certify that this paper is being deposited with the United States Postal Service ' Express Mail Post Office To Addressee service under 37 CFR 1.10 and is addressed to Box Patent Application, U.S. Patent and Trademark Office, P. O. Box 2327, Arlington, VA 22202.

By: Isabell Ogata
Name: Isabell Ogata